

ORANGE PEEL GRAPPLE PACKAGES



- The robust orange peel grapple is used for bulky scrap, building materials and handling facilities – according to the application it is available with different tine shapes and volumes
- PZG-PH: Half closing tines – closing at the lower part of the segments – for handling swarf, scrap, rubbish, waste paper, etc.
- Long service life due to the robust design
- Powerful operation with the high closing force of 11 – 13 kN at 260 bar operating pressure

TECHNICAL SPECIFICATIONS

Type	Number of tines	Volume (litre)	Opening width (mm)	Width (mm)	Height (mm)	Closing force (kN)	Load capacity (kg)	Self weight (kg)
PZG120PH4-PK	4	120	1360	1065	800	13	2000	298
PZG180PH4-PK	4	180	1450	1070	850	12	2000	308
PZG240PH4-PK	4	240	1720	1125	985	11	2000	338
PZG120PH5-PK	5	120	1360	1065	800	13	2000	338
PZG180PH5-PK	5	180	1450	1070	850	12	2000	343
PZG240PH5-PK	5	240	1720	1125	985	11	2000	378

SCOPE OF DELIVERY: Orange peel grapple, flange rotator, suspension, connecting hoses and non-return valve

TRUCK CRANE REQUIREMENTS

Operating pressure: max. 260 bar
Pressure limitation: 260 bar
Pump capacity: 30 – 75 l/min
Two hydraulic functions on the crane

NOTE:

For further types of grapples and additional technical information please turn to page 70.